



WARNING

Do not use Boom if plunger is not engaged in the locating hole.



WARNING

Never exceed the rated capacity at any station. Doing so may cause the lift to become unstable.

| Dimensions | 2112 | | 2118 | | 2124 | |
|------------------------------------|----------|----------|----------|----------|----------|----------|
| Height - stowed | 84" | 213.4 cm | 84" | 213.4 cm | 84" | 213.4 cm |
| Length - stowed | 34" | 86.4 cm | 34" | 86.4 cm | 34" | 86.4 cm |
| Height - operating | 84" | 213.4 cm | 84" | 213.4 cm | 84" | 213.4 cm |
| Length - operating | 62" | 157.5 cm | 73" | 185.4 cm | 73" | 185.4 cm |
| Base width | 31.25" | 79.4 cm | 31.25" | 79.4 cm | 31.25" | 79.4 cm |
| Width with stabilizer legs | 74" | 188.0 cm | 74" | 188.0 cm | 74" | 188.0 cm |
| Ground clearance | 2.5" | 6.4 cm | 2.5" | 6.4 cm | 2.5" | 6.4 cm |
| Load height (minimum) | 6" | 15.2 cm | 6" | 15.2 cm | 6" | 15.2 cm |
| Maximum height (forks down) | 11'1" | 3.4 m | 16'6" | 5.0 m | 21'11" | 6.7 m |
| Maximum height (forks reversed) | 13'1" | 4.0 m | 18'6" | 5.6 m | 23'11" | 7.3 m |
| Weight | | | | | | |
| Net weight | 252 lbs. | 114.5 kg | 321 lbs. | 146 kg | 366 lbs. | 166 kg |
| Load Capacity | | | | | | |
| Load capacity, 14" load center | 650 lbs. | 300 kg | 650 lbs. | 300 kg | 650 lbs. | 300 kg |
| Load capacity with fork extensions | 200 lbs. | 90 kg | 200 lbs. | 90 kg | 200 lbs. | 90 kg |
| Fork Specifications | | | | | | |
| Standard fork width | 21.5" | 54.6 cm | 21.5" | 54.6 cm | 21.5" | 54.6 cm |
| Standard fork length | 28" | 71.1 cm | 28" | 71.1 cm | 28" | 71.1 cm |
| Fork length with extensions | 42" | 106.7 cm | 42" | 106.7 cm | 42" | 106.7 cm |
| Fork weight | 32 lbs. | 14.5 kg | 32 lbs. | 14.5 kg | 32 lbs. | 14.5 kg |
| Fork weight with extensions | 38 lbs. | 17.3 kg | 38 lbs. | 17.3 kg | 38 lbs. | 17.3 kg |

LOAD CAPACITY CHART
2100 Series Lift

