



A+++

RMRB



Full touch screen
 simple wire controller



Heating Capacity

RMAW-03FR1-V (SPLIT) | RMAW-03ZR1-V (MONOBLOK)

Ambient temperature(°C)	Water temperature		
	30/35 °C	40/45 °C	50/55 °C
-25 °C	3,96	3,77	3,7
-20 °C	5,17	4,84	4,34
-15 °C	6,03	5,74	5,17
-7 °C	7,06	6,72	6,46
2 °C	7,75	7,38	7,23
7 °C	9,43	8,2	7,38
12 °C	9,9	9,43	9,24
20 °C	10,76	10,25	9,84

COP

RMAW-03FR1-V (SPLIT) | RMAW-03ZR1-V(MONOBLOCK)

Ambient temperature (°C)	Water temperature		
	30/35 °C	40/45 °C	50/55 °C
-25 °C	1,71	1,50	1,26
-20 °C	2,41	2,14	1,51
-15 °C	2,73	2,34	1,82
-7 °C	3,47	2,97	2,28
2 °C	3,77	3,23	2,75
7 °C	4,40	3,45	2,95
12 °C	4,72	4,04	3,30
20 °C	5,05	4,35	3,48

Heating capacity

RMAW-04FR1-V (SPLIT) | RMAW-04ZR1-V (MONOBLOCK)

Ambient temperature (°C)	Water temperature		
	30/35 °C	40/45 °C	50/55 °C
-25 °C	5,22	4,97	4,87
-20 °C	6,8	6,37	5,72
-15 °C	7,94	7,56	6,8
-7 °C	9,30	8,86	8,50
2 °C	10,21	9,72	9,53
7 °C	12,42	10,8	9,72
12 °C	13,04	12,42	12,17
20 °C	14,18	13,5	12,96

COP

RMAW-04FR1-V (SPLIT) | RMAW-04ZR1-V (MONOBLOK)

Ambient temperature (°C)	Water temperature		
	30/35 °C	40/45 °C	50/55 °C
-25 °C	1,73	1,51	1,28
-20 °C	2,44	2,16	1,53
-15 °C	2,76	2,37	1,84
-7 °C	3,51	3,01	2,31
2 °C	3,81	3,27	2,78
7 °C	4,45	3,48	2,99
12 °C	4,77	4,09	3,34
20 °C	5,13	4,40	3,52

Heating capacity

RMAW-05FR3-V (SPLIT) | RMAW-05ZR3-V (MONOBLOCK)

Ambient temperature (°C)	Water temperature		
	30/35 °C	40/45 °C	50/55 °C
-25 °C	8,11	7,73	7,57
-20 °C	10,8	9,91	8,89
-15 °C	12,35	11,76	10,58
-7 °C	14,46	13,78	13,22
2 °C	15,88	15,12	14,82
7 °C	19,32	16,8	15,12
12 °C	20,29	19,32	18,93
20 °C	22,05	21,00	20,16

COP

RMAW-05FR3-V (SPLIT) | RMAW-05ZR3-V (MONOBLOCK)

Ambient temperature (°C)	Water temperature		
	30/35 °C	40/45 °C	50/55 °C
-25 °C	1,71	1,50	1,27
-20 °C	2,42	2,15	1,51
-15 °C	2,74	2,35	1,82
-7 °C	3,48	2,98	2,29
2 °C	3,78	3,24	2,76
7 °C	4,42	3,46	2,96
12 °C	4,73	4,06	3,31
20 °C	5,09	4,36	3,49

Heating capacity

RMAW-06FR3-V (SPLIT) | RMAW-06ZR3-V (MONOBLOCK)

Ambient temperature (°C)	Water temperature		
	30/35 °C	40/45 °C	50/55 °C
-25 °C	8,79	8,37	8,2
-20 °C	11,47	10,74	9,63
-15 °C	13,38	12,74	11,47
-7 °C	15,67	14,92	14,33
2 °C	17,2	16,38	16,05
7 °C	20,93	18,20	16,38
12 °C	21,98	20,93	20,51
20 °C	23,89	22,75	21,84

COP

RMAW-06FR3-V (SPLIT) | RMAW-06ZR3-V (MONOBLOCK)

Ambient temperature (°C)	Water temperature		
	30/35 °C	40/45 °C	50/55 °C
-25 °C	1,71	1,50	1,26
-20 °C	2,41	2,14	1,51
-15 °C	2,73	2,34	1,82
-7 °C	3,47	2,98	2,29
2 °C	3,77	3,23	2,75
7 °C	4,40	3,45	2,95
12 °C	4,72	4,04	3,30
20 °C	5,08	4,35	3,48

Heating capacity

RMAW-08ZR3-V (MONOBLOCK)

Ambient temperature (°C)	Water temperature		
	30/35 °C	40/45 °C	50/55 °C
-25 °C	10,38	9,89	9,69
-20 °C	13,55	12,69	11,38
-15 °C	15,80	15,05	13,55
-7 °C	18,51	17,63	16,92
2 °C	20,3	19,35	18,96
7 °C	24,73	21,50	19,35
12 °C	25,96	24,73	24,23
20 °C	28,22	26,88	25,80

COP

RMAW-08ZR3-V (MONOBLOCK)

Ambient temperature (°C)	Water temperature		
	30/35 °C	40/45 °C	50/55 °C
-25 °C	1,71	1,50	1,26
-20 °C	2,41	2,14	1,51
-15 °C	2,73	2,34	1,82
-7 °C	3,47	2,97	2,28
2 °C	3,77	3,23	2,75
7 °C	4,40	3,45	2,95
12 °C	4,72	4,04	3,30
20 °C	5,08	4,35	3,48

Heating capacity RMAW-10ZR3-V (MONOBLOCK)

Ambient temperature (°C)	Water temperature		
	30/35 °C	40/45 °C	50/55 °C
-25 °C	14,83	14,14	13,85
-20 °C	19,36	18,12	16,26
-15 °C	22,58	20,50	19,36
-7 °C	26,45	25,19	24,18
2 °C	29,03	27,65	27,10
7 °C	35,33	30,80	27,65
12 °C	37,08	35,33	34,62
20 °C	40,32	38,40	36,86

COP

RMAW-10ZR3-V (MONOBLOCK)

Ambient temperature (°C)	Water temperature		
	30/35 °C	40/45 °C	50/55 °C
-25 °C	1,62	1,42	1,20
-20 °C	2,29	2,03	1,43
-15 °C	2,60	2,22	1,73
-7 °C	3,30	2,83	2,17
2 °C	3,58	3,07	2,62
7 °C	4,18	3,27	2,81
12 °C	4,48	3,84	3,14
20 °C	4,82	4,13	3,31